

# H50DA EXPLORER



## CARACTERISTICAS TECNICAS

(Technical details - Technische daten - Caractéristiques techniques)

Capacidad Nominal (Nominal capacity, Tragkraft, Capacité)	3300 kgr.
Centro de carga (Load center, Lastschwerpunkt, Centre de charge)	500 mm.
Ruedas (Kind of wheels, Reifen, Type de Roues)	(P=Pneumáticas) P/P (P=Pneumatics, Luftreifen, Pneumatique)
Ruedas motrices (Driving wheels, Antriebsreifen, Roues motrices)	2/2
Mástil standard (Standard mast, Hubmast standard, Mât standard)	4000 mm.
Portahorquillas (Forks carriage, Gabelträger, Tablier)	FEM 4 B
Longitud horquillas (Forks length, Gabellänge, Longueur fourches)	1200 mm.
Longitud total hasta portahorquillas (Total length up to the carriage, Länge bis zum Gabelträger, Longueur jusqu'au tablier)	3580 mm.
Ancho total (Total width, Breite, Largeur)	1970 mm.
Altura total (Total height, Höhe, Hauteur)	2200 mm.
Altura asiento conductor (Driver seat height, Fahrer Sitz Höhe, Hauteur siege conducteur)	1230 mm.
Radio de giro (Turning radius, Wendekreis halbmesser, Rayon de braquage)	2985 mm.
Distancia de carga (Load distance, Last Abstand, Distance de charge)	655 mm.
Anchura pasillo (Aisle width, Wandelgang Breite, Largeur de passage)	(AST 800x1200) 3900 mm.
Pendiente superable (Gradeability, Ersteigbarer Hang, Pente superable)	32 %
Peso total (Total weight, Gewicht, Poids total)	7660 Kg.
Paso (Wheels base, Achse Entfernung, Passage)	2090 mm.
Altura libre al suelo (Ground clearance, Bodenfreiheit, Hauteur libre au sol)	400 mm.
Motor (Engine, Motor, Moteur)	PERKINS 1104C.44-T (4 cil. / 4.400 cm <sup>3</sup> / 74,5 Kw. / 100 cv/hp)
Transmisión (Transmission, Getriebe, Transmission)	HIDROSTATICA AUTOMOTIVE HP (Hydrostatic, Hydrostat, Hydrostatique)
Mástiles disponibles (Masts, Mâts)	4000 DUPLEX /// 3800 - 5000 TRIPLEX

